







Manufactured in France

1 temperature cabinet

Large size

**Premium Pack** 



1 YEAR WARRANTY

Maturing cabinet, for ageing or serving wine

# **Technical Specifications**

Capacity

106 or 124 maximum bottles\*

Temperature and Hygrometry

Setting range from 6 to 18°C

· At 12°C, independently regulated hygrometry at 70%

Design

- · Triple glazed and anti UV Full Glass door. Not reversible. Right or left opening > Choice on order
- Inner lighting: ambiance lighting by 4 LED under each shelf and 2 LÉD under the control panel (3 options: permanent, when opening door, disabled). 3 levels of light intensity
- · Handle integrated in the door profile
- · LED screen with sensitive keys

Standard shelf



9 Bordeaux bottles

11 covering available

7 Bordeaux bottles + 2 Magnum bottles

#### Regulation and equipement

- · Electronic regulation
- Internal display and settings
- · Temperature display
- · Hygrometry display, non adjustable.
- · Display only at 12°C
- · Alarms in case of dysfunction (open door, sensor fault, temperature dysfunction, hygrometry dysfunction, need to fill the humidity tank, need to replace charcoal filter)
- · Default ECO mode (= screen saver)

- · Automatic defrost
- · On/Off/ switch
- · Active charcoal filter 150x150 mm
- · 4 adjustable shock absorbing feet + 4 embellishments
- · Condensate discharge pipe
- Autonomous hygrometry regulation tank «Hygrocontrol System». Patented system
- · Frost protection thermostat



Covering



Sliding shelf ACMSR

Earth



Châtaigner





Argent



Calacatta

















Noir Touch



Roche

Accessories

· 11 sliding shelves + 1 fixed, with black tinted ash front

· Sliding shelves equipped with a soft close device

· 8 mains du Sommelier at the bottom of the cabinet

6 removable bottle identifiers per sliding shelf

· 1 erasable felt tip marker

Mixed air/ Variable speed

compressor R600a gas

CE/US/UK/IA/AU/CH/C6

1 key ring

-1 microfiber cloth

Technologies **Cold production:** 

Cords:

**Heat production:** Heat release:

Resistance Automatic

45W resistor

Inner material:

Aluminium HPL panel (High pressure laminated)

Exterior coating material: Insulation type:

Injected polyurethane foam (59 mm)





### General features

Full Glass door		
340		
250		
1847 x 880 x 617***		
2000 x 970 x 700		
Standard : Red Earth, Mineral Grey Optional : 9 colors		
	340 250 1847 x 880 x 617*** 2000 x 970 x 700 Standard : Red Earth, Mineral Grey	

<sup>\*\*</sup>Equipped cellar weight \*\*\*+23mm with rear stop

## Energy efficiency & Consumption

Cords	230V-50Hz	115V-60Hz	
Type of door	Full Glass	Full Glass	
Energy efficiency class	Е	/	
Annual energy consumption AEC (Kwh/year)	100	85	
Sound emission (dB(A))	34 (steady state)	34 (steady state)	
Sound emission Class	В	/	
Ambient operating temperature (°C)	5-35	5-35	
Useful volume (litres)	421		

For a "service" usage, with an inner temperature between 6-9°C, we recommend to not place Royale in an ambient environment above 30°C/70% HR.

Royale, in a few words...

# Why Royale?

Quite simply because it represents the best we can offer our customers in terms of performance, durability and aesthetics.



